

# SUBMITTAL DATA - INDOOR UNIT **VWMD005S6-5**P

VRF Ductless Wall Mounted

Job:	E	ngine	er:			
Location:	Architect:					
Schedule No.:		ocatio	on:			
System Designation:	D	Date:				
	F	or:	Reference	Approval	Review	Construction

# Wall Mounted Ductless Indoor Unit

### **FEATURES**

- Temperature Display • 4-Way Swing
- · Washable filter included • Refrigerant R-32
- Advanced Commissioning and Service
- Compatible with VRF air and water source products
- Nine capacity sizes from 5,000 to 32,000 Btu/h

#### WARRANTY

• 10-year limited warranty.\*See warranty for details.

SPECIFICATIONS			
PERFORMANCE			
Cooling Capacity <sup>1</sup> (Btu/h)	5,000		
Heating Capacity <sup>1</sup> (Btu/h)		5,800	
Airflow (CFM)	Low/Medium/High	145/159/173	
External Static Pressure		0	
(in. WC)			
Sound (dBA)	Low/Medium/High	27/30/31	
ELECTRICAL DATA			
Power Supply (Volts/Hertz	208-230/60/1		
Minimum Circuit Ampacity	0.16		
Maximum Overcurrent Pro	15		
Cooling Power Input <sup>2</sup> (W)	20		
Cooling Rated Current (A)	0.13		
Heating Power Input <sup>2</sup> (W)	20		
Heating Rated Current (A)		0.13	
Fan Motor Output (W)	27 x 1		
DIMENSIONS			
Unit Dimensions (in)	Width	32.3	
	Height	11.8	
	Depth	8.5	
Liquid Pipe Connection (in	) (I.D)	1/4	
Gas Pipe Connection (in)	(I.D.)	1/2	
Net Weight (lb)		19.8	
Shipping Weight (lb)		23.1	

OPTIONAL ACCESSORIES	
VSTAT02P-1 Touch Screen Wired Controller	37P79
VSTAT04P-1 Individual Wired Controller	37Y74
VSTAT01P-1 Wireless Remote Controller	37Y73



### **NOTES**

- •Specification may be subject to change without prior notice.
- 1)Performances are based on the following test conditions.
- -Cooling: Indoor temperature: 80°F(26.7°C) DB, 67°F(19.4°C)
- WB, Outdoor temperature : 95°F(35°C) DB, 75°F(23.9°C) WB -Heating: Indoor temperature: 70°F(21.1°C) DB, 60°F(15.6°C)
- WB, Outdoor temperature: 47°F(8.3°C) DB, 43°F(6.1°C) WB
- -Equivalent refrigerant piping length 7.5m(24.6ft), Level
- differences: 0m(0ft))
- 2)Sound level was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.
- 3)These products contain R32 (GWP=675) which is fluorinated greenhouse gas.
- 4)Select wire size based on the value of MCA









## VWMD005S6-5P VRF Ductless Wall Mounted

## DIMENSIONAL DRAWINGS - MM (Inches)



