

Submittal Data

MMD024M6-1P (JNG24ZDD)

Multi-Position Air Handler

Job Name: _____
 Purchaser: _____
 Submitted to: _____
 Unit designation: _____

Location: _____
 Engineer: _____
 Reference: _____ Approval _____ Construction _____
 Schedule #: _____

General Information

- The system shall have a built-in Wi-Fi adapter as standard to allow control and monitoring using the Samsung SmartThings app.
- The outdoor unit shall supply power to indoor unit via 14 AWG X 3 power wire (when accessory electric heat kits are not installed).

Construction

- Insulated, galvanized steel.

Refrigerant System

- The heat exchanger shall be mechanically bonded aluminum fin to copper tube.
- Refrigerant flow shall be controlled by electronic an expansion valve at the outdoor unit
- The system shall include an R32 alarm output plug on the indoor unit and outdoor unit for notification of R32 leak detection (VSTAT10P-1 accessory is required).

Indoor Fan

- Three fan speeds and auto setting

Controls

- Control wiring shall be 2 X 16 AWG wire.
- The unit shall be operated via a wireless or wired remote control with DDC type signal.
- Dual set temperature support when connected to supported controllers.
- Wired or wireless controllers must be purchased separately.

External Heat Control

- External heat control functionality allows for configuration of fan operation during auxiliary heat operation, defrost, and emergency heat (VSTAT10P-1 accessory required when controlling heating devices other than V1EHK**-1P electric heat kits).
- External heat control configuration settings include outside ambient external heat lockout, outside ambient compressor lockout, and time delay options (VSTAT10P-1 accessory required when controlling heating devices other than V1EHK**-1P electric heat kits).



Note: Unit appearance may vary slightly

- Emergency heat functionality allows the system to continue controlling the external heat source even when system errors prevent the heat pump from operating (VSTAT10P-1 accessory required when controlling heating devices other than V1EHK**-1P electric heat kits).
- External heat control functionality allows for configuration of fan operation during auxiliary heat operation, defrost, and emergency heat
- Emergency heat functionality allows the system to continue controlling the external heat source even when system errors prevent the heat pump from operating

Convenience

- Emergency Temperature Output (ETO) function: when indoor unit is in error status or when room temperature exceeds configurable temperature level, the system outputs a signal to an external source, e.g., backup system, building management system, alert device (ex: status light, warning lamp, buzzer).



Intertek

Specifications

Model	US Code		JNG24ZDD
	Model Number		MMD024M6-1P
Performance	Nominal Capacity	Cooling (Btu/h)	24,000
		Heating (Btu/h)	27,000
Power	Voltage	ø / V / Hz	1 / 208-230 / 60
	Operating Current (max.)	Cooling (A)	1.5
		Heating (A)	1.5
Evaporator Fan	Type		Constant Torque With Double-inlet, Forward Curve, Centrifugal Fan
	Output	Watts	153
	External Static Pressure	Standard ("WC)	0.58
		Min. / Max. ("WC)	0 / 0.8
Airflow	Air Volume (L/M/H)	Cooling (CFM)	548 / 636 / 759
		Heating (CFM)	548 / 636 / 759
Refrigerant	Type		R-32
	A2L Leak Detection		Integral
Pipe Connections	Indoor & Outdoor	High side	1/4
		Low side	5/8
	Condensate Connection		3/4" FNPT
Dimensions	W X H X D	In.	17 1/2 X 43 X 21
	Weight	lbs.	98.10
	Duct Connections (W X H)	Supply (in.)	12 1/2 X 15 1/2
		Return (ID, in.)	17 1/2 X 21
Operating Temperatures	Indoor	Cooling	64 ~ 90°F (16 ~ 32°C)
		Heating	T ≤ 86°F (30°C)
Sound Pressure Level	Low / Med. / High	dB(A)	37 / 40 / 43
Safety	Certifications		UL 60335-2-40

Accessories

Wired controller	Advanced	VSTAT04P-1
	Touchscreen	VSTAT02P-1
Thermostat adapter (for connection to standard 24VAC thermostats)		VSTAT09P-1
Wireless signal control	Wireless signal receiver	VCTRL10P-1
	Wireless controller	VSTAT01P-1
External temperature sensor		VCTRL11P-1
External contact control interface module		VSTAT10P-1
Filter base		V1FBS01-4P
Supplemental electric heat kit	3kW	V1EHK01-1P
	5kW	V1EHK02-1P

Dimensional Drawing
MMD024M6-1P (JNG24ZDD)

Unit: Inches

