

# Product Disclaimers and Testing

---

- 1 Based on sound pressure levels during steady-state, high-fire and low-fire operation of Lennox® SLP99UH070XV36B as of March 2020 at mid-point temperature rise and minimum external static pressure when set up per Section 4.4.4 of AHRI 260-2012. Based on AFUE efficiency rating of Lennox SLP99UH090XV60C and leading competitive units listed in AHRI directory as of December 2019. Efficiency ratings established per test standard ANSI/ASHRAE 103-1993.
- 2 Based on sound pressure levels during steady-state, high-fire operation of Lennox SL280UHV070V36A and leading competitive units at mid-point temperature rise and minimum external static pressure when set up per Section 4.5.3 of AHRI 260-2001, as of December 2019.
- 3 Stainless steel secondary heat exchanger.
- 4 Efficiency claim based on comparison of the average SEER2 of the SL25KCV as compared to the average SEER2 of the competitive variable capacity compressor units as published in AHRI (September 2024). Actual system efficiency may vary based on the system match and other factors; consult AHRI Directory for exact system efficiency. Precision claim based on the average cooling capacity range of the SL25KCV as compared to the average published cooling capacity of competitive 20 SEER2+ variable capacity compressor units (September 2024). Averages calculated across the full tonnage range available.
- 5 Efficiency ratings established per AHRI's test standard: ANSI/AHRI 210/240-2017 of two-stage central AC/HP equipment as published in AHRI (December 2019).
- 6 Efficiency claim based on comparison of the combined heating and cooling efficiency within a single product family (HSPF2, EER2, and SEER2 of the SL22KLV) as compared to the HSPF2, EER2, and SEER2 of competitive R-454B and R-32 ducted heat pump as published in AHRI (January 2025). Actual system efficiency may vary based on the system match and other factors; consult AHRI Directory for exact system efficiency. Precision claim based on the average cooling capacity range of the SL22KLV as compared to the average cooling capacity range of the competitive variable capacity compressor units based on published competitive data (January 2025). Cooling capacity ranges calculated across 2, 3, 4 and 5 tonnage at maximum and minimum speed at ARI standard rating conditions: 95°F outdoor and 80°/67° indoor (80°F dry bulb and 67°F wet bulb).
- 7 (Not Applicable)
- 8 Covered components may be eligible to receive a 10-year warranty. Online equipment registration at [www.warrantyourway.com](http://www.warrantyourway.com) is required within 60 days of installation (except in California and Quebec) or Lennox' base warranty will apply. Applies to residential applications only. See actual warranty certificate for details.
- 9 This product may be eligible for valuable 12-Year Limited Extended Warranty coverage with product registration.

# Product Disclaimers and Testing

---

- 10 The MWLD, MWHD, and MWPD mini-split heat pumps may be eligible for valuable 12-Year Limited Extended Warranty coverage with product registration. Online equipment registration at [www.lennoxregistration.com](http://www.lennoxregistration.com) is required within 60 days of installation (except in California and Quebec) or Lennox' base warranty will apply. Applies to residential applications only. See actual warranty certificate for details.
- 11 Covered components in the equipment are warranted for 1 year when installed in non-residential applications. Warranty is not applicable to maintenance items.
- 12 Hg-LAMPS contain mercury. Manage in accordance with disposal laws. Refer to [www.lamprecycle.org](http://www.lamprecycle.org) or call 1-800-9-Lennox.
- 13 Removal efficiency based on third party testing results using MS-2 bacteriophage (ATCC 15597-B1). Bacteria representative of virus-sized particles like SARS-CoV-2, the virus that causes COVID-19. November 2020.
- 14 When used properly with other best practices recommended by CDC and others, filtration can be part of a plan to reduce the potential for airborne transmission of COVID-19 indoors.
- 15 Lennox Industries Inc. ("Lennox") is not a tax advisor and does not make any representation, warranty, guarantee or other assurance as to whether a particular matchup qualifies or is eligible for tax credits. Moreover, the tax laws are subject to change. As a result, Lennox highly recommends that you consult with a tax advisor regarding your qualification for the tax credits in your circumstance and verify and review the applicable tax laws and regulations.
- 16 When compared to the other major US HVAC OEMs.
- 17 This product meets ENERGY STAR® requirements when appropriate coil components are used. Ask your contractor for details.

## California Only

This furnace does not meet the South Coast Air Quality Management District (SCAQMD) Rule 1111 NOx emission limit (14 ng/J) and cannot be installed in the SCAQMD.

If installed in San Joaquin Valley Air Pollution Control District (SJVAPCD) only: This furnace does not meet the SJVAPCD Rule 4905 NOx emission limit (14 ng/J), and thus is subject to a mitigation fee of up to \$450.