



REAL COMFORT, REAL CONNECTION, REAL CONTROL

Now featuring R-454B refrigerant, Lennox REAL™ 2.0 delivers flexible, high-performance comfort with the precision and connectivity today's spaces demand. Designed for reliable heating and cooling across multiple zones, REAL™ 2.0 combines advanced heat pump technology with simplified installation and service-friendly design, making it easy to specify, install, and maintain.

Key Features

- Operation down to -22°F in heating
- Sound levels as low as 55 dBA
- Total piping length of 984 ft.*
- 1.5-5 ton single and dual fan heat pump
- Reuse existing line sets
- Precise temperature control
- Connect up to 9 indoor units
- Dual Fuel capability

*Varies on capacity



ONE TO ONE 24V WALL HUNG



Necessary condition:

Outdoor Commissioning	First-Level Menu	Second-Level Menu	Third-Level Menu
Value	1	1	0

Outdoor Commissioning	First-Level Menu	Second-Level Menu	Third-Level Menu
Value	1	0	3

REAL COMFORT

Lennox REAL™ 2.0 provides precise temperature control regardless of the indoor unit style, VRF or traditional.

REAL CONNECTION

Available in 1.5 to 5-ton configurations with options to control up to nine zones.

REAL CONTROL

With multiple control options available it can be customized to create an ideal environment in any zone.

LENNOX REAL™ 2.0 PERFORMANCE SPECIFICATIONS

		COOLING DATA					HEATING DATA			PHYSICAL DATA		OPERATION DATA	
NOM. TON	MODEL NUMBER	CAPACITY (BTU/H)	SEER2		EER2		CAPACITY (BTU/H)	HSPF2		DIMENSIONS W x H x D (IN.)	NET WT. (LBS.)	HEATING (°F)	COOLING (°F)
			Ducted	Non-Ducted	Ducted	Non-Ducted		Ducted	Non-Ducted				
1.5	VPC018H5M-3P	18,200	17	17.5	11.7	12	20,000	9	10	39-1/8 x 28 x 16-3/4	121	-22°F to 86°F	5°F to 118°F
2	VPC024H5M-3P	22,000	17	18.5	11.7	11.7	25,000*	9	10	39-1/8 x 28 x 16-3/4	121		
2.5	VPC030H5M-3P	30,000	17.8	20	12	14	30,000	9.8	10.1	40-11/16 x 34 x 20-9/16	207		
3	VPC036H5M-3P	36,000	17.8	20	12	13.3	40,000	9.6	10.1	40-11/16 x 34 x 20-9/16	207		
4	VPC048H5M-3P	47,000*	17.6	20	11.7	11.7	50,000	10	10.1	38-1/2 x 52-1/4 x 15-3/4	227		
5	VPC060H5M-3P	60,000	17	19.5	9	9.5	60,000	9.2	10.1	52-1/4 x 36 x 15-3/4	227		

*Applicable to ducted system types only

CONTACT YOUR LOCAL SALES MANAGER TODAY!

Lennox.com/Commercial