

KEY FEATURES

- Heat Pump and Heat Recovery models
- 208-230V/60Hz/3 Ph or 460V/60Hz/3 Ph
- 6, 8 and 10 ton modules
- Connect up to 3 modules for system capacities up to 24 tons
- Connect up to 64 indoor units
- Wide operating range from 122°F ambient to as low as -22°F
- 100% heating capacity at -22°F



VARIX LOW AMBIENT VRF



Wide variety of indoor unit options



Extended piping length



Available in 6-24 tons capacity

Equipped with Intelligent Defrost Algorithms



Flash Injection Technology

Ill Outdoor units as quiet as 55 dBA

HEAT PUMP											
VOLTAGE	CAPACITY (TONS)	DIMENSIONS W X D X H	WEIGHT (LBS)	MCA	МОСР	HEATING @ -22°F	HEATING @ -13°F	HEATING	COOLING @ 95°F	EER (DUCTLESS)	IEER (DUCTLESS)
	6	51 x 30-1/8 x 66-3/4	553	50	60	78,000	81,000	81,000	72,000	12.7	23.7
208/230V	8		644	62	70	104,500	108,000	108,000	96,000	12.85	25.1
	10		644	76	90	130,600	135,000	135,000	120,000	12.65	24.9
460V	6		571	25	30	78,000	81,000	81,000	72,000	12.7	23.7
	8		661	31	35	104,500	108,000	108,000	96,000	12.85	25.1
	10		661	38	45	130,600	135,000	135,000	120,000	12.65	24.9

HEAT RECOVERY											
VOLTAGE	CAPACITY (TONS)	DIMENSIONS W X D X H	WEIGHT (LBS)	MCA	МОСР	HEATING @ -22°F	HEATING @ -13°F	HEATING	COOLING @ 95°F	EER (DUCTLESS)	IEER (DUCTLESS)
208/230V	6	51 X 30-1/8 X 66-3/4	567	50	60	78,000	81,000	81,000	72,000	12.7	23.7
	8		659	62	70	104,500	108,000	108,000	96,000	12.85	25.1
	10		659	76	90	130,600	135,000	135,000	120,000	12.65	24.9
460V	6		584	25	30	78,000	81,000	81,000	72,000	12.7	23.7
	8		677	31	35	104,500	108,000	108,000	96,000	12.85	25.1
	10		677	38	45	130,600	135,000	135,000	120,000	12.65	24.9

EXPERTISE THAT RISES ABOVE.

With high efficiencies in extreme cold-weather environments, virtually silent operation and independent setpoint control for up to 64 zones, Varix[™] Low Ambient VRF offers many advantages for you and your customers. More performance and flexibility for your customers means more opportunities for you.



Note - Due to our ongoing commitment to quality, all specifications, ratings and dimensions are subject to change without notice.

Learn more about Low Ambient VRF at Lennox.com/commercial 38Y93 4/25