

SUBMITTAL DATA - INDOOR UNIT VVC**D**030**S**4-**5**P

VRF Heat Pump & Heat Recovery

Job:	Engineer:			
Location:	Architect:			
Schedule No.:	Location:			
System Designation:	Date:			
	For: Peteroneo	Approval	Poviow	Construction

Vertical Air Handler Ducted Indoor Unit

FEATURES

- Flexible Installation
 Improve Air Quality
- · Increased Static Pressure
- Advanced Commissioning and Service

- Multiposition
- · Supplemental Heat
- · Refrigerant R-32
- · Compatible with VRF Water or Air Source Products

WARRANTY

• 10-year limited warranty.*See warranty for details.

SPECIFICATIONS			
PERFORMANCE			
Cooling Capacity ¹ (Btu/h)		30,000	
Heating Capacity1 (Btu/h)		34,000	
Airflow (CFM) Low/Medium/High		758/875/1053	
External Static Pressure (in. WC)	0.1~1.0		
Refrigerant Type		R-32	
Sound Pressure (dBA)	Low/Medium/High	38/40/42	
ELECTRICAL DATA			
Power Supply (Volts/ Phase/Hertz)		208/230V-1Ph-	
		60Hz	
Power Source Wire (No Heater)		14 AWG	
Transmission Cable		16 AWG	
Cooling Power Input (W)		218	
Cooling Current Input (A)		1.58	
Heating Power Input (W)		218	
Heating Current Input (A)		1.58	
Fan Motor Output x n (W)		410 x 1	
DIMENSIONS			
Unit Dimensions (in)	Height	48	
` ,	Width	21	
	Depth	21	
Liquid Pipe Connection (in)	3/8		
Gas Pipe Connection (in)	5/8		
Condensate Drain Connection (in)	FPT 3/4		
Unit Shipping Weight (lb)	135		
1 1 !4 N 1 - 4 N A / - ! l- 4 / H- N		101	



OPTIONAL ACCESSORIES			
V1FBS02-4P, VVC030-036 & MMD018-036 Filter Base	38B69		
XFÒPS€-ÆÚ, 5kW Electric Heat Kit	38X€		
VSTAT02P-1 Touch Screen Wired Controller	37P79		
VSTAT04P-1 Individual Wired Controller	37Y74		
VSTAT01P-1 Wireless Remote Controller	37Y73		
XFÒPS€I ËFÚ, F€kW Electric Heat Kit	38X € Í		

NOTES

Unit Net Weight (lb)

- Nominal capacity are based on (Refrigerant Piping 25ft, Level Differences 0ft);
 - . Cooling : Indoor temperature 80°F DB, 67°F WB / Outdoor temperature 95°F DB, 75°F WB
 - . Heating : Indoor temperature 70°F DB, 60°F WB / Outdoor temperature 47°F DB, 43°F WB
- Sound pressure was acquired in a dead room. Thus actual noise level may be different depending on the installation conditions.








SUBMITTAL DATA - INDOOR UNIT **VVCD030S4-5P**

VRF Heat Pump & Heat Recovery

DIMENSIONAL DRAWINGS - MM (Inches)



No.	Name	Description
1	Gas pipe connection	Ф15.88(5/8)
2	Liquid pipe connection	Ф9.52(3/8)
3	Drain pipe connection	FPT 3/4
4	Air outlet	
5	Air intake	