

V1V22D01CPWW4Way 2x2 White CST Panel V22D005-020, M22D9/18


Job name:	Location:			
Purchaser:	Engineer:			
Submitted to:	Reference_	Approval	Construction	
Unit designation:	Schedule #:			

Specifications

- Fascia panel for Lennox calm air mode Mini 4-Way Cassette indoor units
- The fascia panel shall include an integral Wi-Fi adapter as standard for indoor unit remote monitoring and control via Samsung SmartThings (R32 models and R410A CAC models that support single Wi-Fi adapter connection).
- HIPS chassis certified to UL94 V0
- 4 X motorized, auto swing louvers with independent louver control capability (32° 65° louver control range)
- Built-in IR receiver for optional wireless control (purchased separately).
- LED status display
- Accommodates Lennox Powered by Samsung motion sensor (V1MDS**CS) for occupancy sensing capability (refer to indoor unit technical documents for compatible MDS model number)
- The panel shall include 1 X washable, pleated filter and all necessary mounting hardware as standard.
- Panel corners are removable to easily level unit and adjust height
- Fascia panel is powered and controlled by the indoor unit PCB

Dimensions

L X W X H (inches)	24 3/8 X 24 3/8 X 2 3/8
Weight (lbs.)	6



Lennox maintains a policy of ongoing development. Specifications are subject to change without notice.