

SUBMITTAL DATA - CONTROLS F1943L-3P (19B16) VRF Heat Pump & Heat Recovery

Job: Location:

Schedule No.:

Architect: Date:

Engineer:

For: Reference Approval Review Construction

VRF Wi-Fi Controller

FEATURES AND FUNCTIONS

- 4" Capacitive Color Touch IPS LCD Screen
- · Relative Humidity Control

System Designation:

- · Operation Mode: Cool / Heat / FAN
- · Display Setpoint, Room Temperature, and Relative Humidity
- · Lockable UI
- · Wi-Fi Provisioning using BLE and Smartphone App
- · Over-the-Air Configurable
- · Heating and Cooling Setpoints

WARRANTY

• 1-year limited warranty. *See warranty for details.

SPECIFICATIONS	
PERFORMANCE	
Input Voltage (V)	12 VDC
Setpoint Range	62°F ~ 86°F
Ambient Temperature Range	32°F ~ 113°F
Ambient Humidity Range (RH)	5% ~ 90%

DIMENSIONS		
Unit Dimensions (in)	Height	3-5/8
	Width	5
	Depth	7/8
CABLING		
Communication Cabling		18 gauge, shielded 4-wire cable





SUBMITTAL DATA - CONTROLS F1943L-3P (19B16) VRF Heat Pump & Heat Recovery

DIMENSIONAL DRAWINGS - INCHES (MM)



