Mini-Split Configurations



Single/Multi-Zone | R-32 | 60 Hz RESIDENTIAL / COMMERCIAL PRODUCT SPECIFICATIONS (EHB)

SINGLE ZONE WALL-MOUNT SYSTEMS

MWLD Cold Climate Wall Only
SEER2 up to 25.0 | HSPF2 up to 11.0
0.75 to 2 Tons
Heating down to -22°F (-30°C)

MWPD High Efficiency Wall Only SEER2 up to 25.0 | HSPF2 up to 11.0 0.75 to 2 Tons MWHD Standard Efficiency Wall Only SEER2 up to 25.0 | HSPF2 up to 10.0 0.75 to 2 Tons



MWLD Outdoor Unit



MWPD Outdoor Unit



MWHD Outdoor Unit



MWMD Wall-Mount Non-Ducted Indoor Unit



MWMD Wall-Mount Non-Ducted Indoor Unit



MWHD Wall-Mount Non-Ducted Indoor Unit

CONTROLLERS



VSTAT01P-1 Wireless Remote Controller (Furnished)



VSTAT02P-1 Touchscreen Wired Controller (Optional)



VSTAT04P-1 Programmable Wired Controller (Optional)

ACCESSORIES

Equipment Pads Equipment Stands Hail Guards Line Sets Control Wiring Wind Baffles Wall Brackets SpeediChannel™ System Disconnects Whips Thermostat Adaptor (24V) for standard thermostat control



SINGLE ZONE SYSTEMS

MMLD Cold Climate

SEER2 up to 23.8 | HSPF2 up to 10.7 0.75 to 4 Tons

Heating down to -13°F (-25°C)

MMPD High Efficiency

SEER2 up to 23.8 | HSPF2 up to 9.6 1.5 to 4 Tons



MMLD Outdoor Unit



MMPD Outdoor Unit



MDDD High Static or MMDD Medium Static **Ducted Indoor Unit**



MDDD High Static **Ducted Indoor Unit**



M22D or M33D Four-Way Cassette Non-Ducted Indoor Unit



M33D Four-Way Cassette Non-Ducted Indoor Unit



M1WD One-Way Cassette Non-Ducted Indoor Unit





MFMD Floor-Mount Console Non-Ducted Indoor Unit





MMD Multi-Position Air Handler

MMD Multi-Position Air Handler

CONTROLLERS



VSTAT01P-1

Wireless Remote Controller (Furnished with Wall-Mount and Floor-Mount Console Models (optional for all other indoor units)



VSTAT02P-1 Touchscreen Wired Controller (Optional)



VSTAT04P-1 Programmable Wired Controller (Optional)

ACCESSORIES

Equipment Pads Equipment Stands Hail Guards Line Sets

Control Wiring Wind Baffles Wall Brackets SpeediChannel™ System


Disconnects Whips Thermostat Adaptor (24V) for standard thermostat control

MULTI-ZONE SYSTEMS

MMLD Cold Climate (up to Four Zones)

SEER2 up to 23.0 | HSPF2 up to 10.5 1.5 to 3 Tons

Heating down to -13°F (-25°C)





MMLD Outdoor Unit



MMPD Outdoor Unit



MDDD High Static or MMDD Medium Static **Ducted Indoor Unit**



MDDD High Static or MMDD Medium Static **Ducted Indoor Unit**



M22D Four-Way Cassette Non-Ducted Indoor Unit




M22D Four-Way Cassette Non-Ducted Indoor Unit



M1WD One-Way Cassette Non-Ducted Indoor Unit



MWHD/MWMD/MWZD Wall-Mount Non-Ducted Indoor Unit



M1WD One-Way Cassette Non-Ducted Indoor Unit



MWHD/MWMD/MWZD Wall-Mount Non-Ducted Indoor Unit



MFMD Floor-Mount Console Non-Ducted Indoor Unit



MFMD Floor-Mount Console Non-Ducted Indoor Unit



MMD Multi-Position Air Handler



MMD Multi-Position Air Handler

CONTROLLERS



VSTAT01P-1 Wireless Remote Controller (Furnished with Wall-Mount and

Floor-Mount Console Models (optional for all other indoor units)



VSTAT02P-1 Touchscreen Wired Controller (Optional)



VSTAT04P-1 Programmable Wired Controller (Optional)

ACCESSORIES

Equipment Pads Equipment Stands Hail Guards Line Sets

Control Wiring Wind Baffles Wall Brackets SpeediChannel™ System Disconnects Whips Thermostat Adaptor (24V) for standard thermostat control

3WPD/3WMD SINGLE ZONE WALL-MOUNT SYSTEMS

3WPD/3WMD Cold Climate

SEER2 - 19.2 | HSPF2 - 8.5 3 Tons Heating down to –13°F (–25°C)




3WPD Outdoor Unit



3WMD Indoor Unit

Controllers



VSTAT01P-1 Wireless Remote Controller (Furnished)



VSTAT02P-1 Touchscreen Wired Controller (Optional)



VSTAT04P-1 Programmable Wired Controller (Optional)

Accessories

Equipment Pads Equipment Stands Hail Guards Line Sets Control Wiring Wind Baffles Wall Brackets SpeediChannel™ System Disconnects
Whips
Thermostat Adaptor (24V) for standard
thermostat control



Visit us at www.Lennox.com
For the latest technical information, www.LennoxPros.com
Contact us at 1-800-9-LENNOX