

Job: _____
 Location: _____
 Schedule No.: _____
 System Designation: _____

Engineer: _____
 Architect: _____
 Location: _____
 Date: _____

For: Reference Approval Review Construction

Wall Mounted Ductless Indoor Unit

FEATURES

- Temperature Display
- 4-Way Swing
- Advanced Commissioning and Service
- Compatible with VRF air and water source products
- Refrigerant R-410A
- Washable filter included
- Nine capacity sizes from 5,000 to 32,000 Btu/h

WARRANTY

- 10-year limited warranty.*See warranty for details.

SPECIFICATIONS

PERFORMANCE

Cooling Capacity ¹ (Btu/h)	15,000
Heating Capacity ¹ (Btu/h)	17,000
Airflow (CFM) Low/Medium/High	370.8/402.6/441
External Static Pressure (in. WC)	0
Sound (dBA) Low/Medium/High	33/34/37

ELECTRICAL DATA

Power Supply (Volts/Hertz/Phase)	208-230/60/1
Minimum Circuit Ampacity (MCA)	0.34
Maximum Overcurrent Protection (MOCP)	15
Cooling Power Input ² (W)	40
Cooling Rated Current (A)	0.27
Heating Power Input ² (W)	40
Heating Rated Current (A)	0.27
Fan Motor Output (W)	27 x 1

DIMENSIONS

Unit Dimensions (in)	Width	41.5
	Height	11.8
	Depth	8.5
Liquid Pipe Connection (in) (I.D.)		1/4
Gas Pipe Connection (in) (I.D.)		1/2
Net Weight (lb)		30.9
Shipping Weight (lb)		26.5

OPTIONAL ACCESSORIES

VSTAT02P-1 Touch Screen Wired Controller	37P79
VSTAT04P-1 Individual Wired Controller	37Y74
VSTAT01P-1 Wireless Remote Controller	37Y73





NOTES

1. Mode : HP (Heat Pump), HR (Heat Recovery)
2. Nominal Cooling : Indoor temperature 26.7°CDB / 19.4°CWB (80°F DB/67°F WB), Outdoor temperature 35°CDB / 23.9°CWB (95°F DB/75°F WB), Refrigerant pipe length 7.5m (25ft), Level difference 0m (0ft).
3. Nominal Heating : Indoor temperature 21.1°CDB / 15.6°CWB (70°F DB/60°F WB), Outdoor temperature 8.3°CDB / 6.1°CWB (47°F DB/43°F WB), Refrigerant pipe length 7.5m (25ft), Level difference 0m (0ft).
4. Sound level was acquired in an anechoic room. Thus actual noise level may be different depending on the installation conditions.
5. These products contain R410A which is fluorinated greenhouse gas.
6. Select wire size based on the value of MCA



DIMENSIONAL DRAWINGS - MM (Inches)



NOTE - Due to Lennox' ongoing commitment to quality, Specifications, Ratings and Dimensions subject to change without notice and without incurring liability. Improper installation, adjustment, alteration, service or maintenance can cause property damage or personal injury. Installation and service must be performed by a qualified installer and servicing agency.